

Kjeltec™ 8200 distillation unit

Automated distillation for Kjeldahl analysis in food and feed



Kjeltec™ 8200 is a fully automated distillation unit designed primarily for Kjeldahl analysis, but widely used for many different distillation chemistries.

A versatile solution that reduces operational costs

A self-adjusting cooling water system saves water and reduces cost, while long-life components ensure minimal downtime. Corrosion-free materials and alkali resistant plastic splash head/tube draining vessel secure long instrument lifetime.

Innovative features and built in safety

Ensure safe operations with patented SAfE feature for safe distillation of samples that form salt cakes and bellow pumps for accurate reagent dispensing. A variable output steam generator broadens the application area to other volatile components.

Secured for your future needs

The Kjeltec™ 8200 can be connected to an optional external titrator. As your business grows the Kjeltec can be upgraded to a fully automated Kjeltec 8400 analyser with a colorimetric titration system and an optional 20 or 60 place sampler.

Sample type

Raw materials and finished products in food, feed and agriculture

Parameters

Nitrogen, protein

Technology

Fully automated distillation for Kjeldahl and other nitrogen based chemical analysis.

Approvals

Officially approved (AOAC, EPA, DIN, ISO) for simplified validation

Specifications

Performance data at 230 V	
Analysis time	3.5 minutes at 30 mg N (6.5 minutes at 200 mg N)
Distillation capacity	~ 40 ml/min at 230 V (at 100 % steam addition)
Measuring range	0.1 – 210 mg N
Reproducibility	1% RSD (including the digestion step)
Recovery	> 99.5% at nitrogen levels between 1 – 200 mg N
Tube draining	200 ml in less than 10 seconds
Reagent pump volume	0 - 150 ml in steps of 10 ml
Delay	0 – 1800 seconds
SAfE (Patented)	0 – 15 seconds
Variable steam addition	30-100 % in steps of 10 %

Installation requirements:	
Power supply	200 – 240 V 50 – 60 Hz
Tolerable voltage variation	± 10 %
Power consumption	2 200 W
Water consumption (during distillation only)	3 l/min at water temp of 25°C * 1 l/min at water temp of 15°C <i>*Circulating Cooler recommended at >25°C</i>
Ambient temperature	5 - 40 °C
Ambient humidity	max. 80% relative
Drain	For cooling water only
Weight net	35 kg
Dimensions (wxdxh) cm	48 x 58 x 69

Accessories

- Titration unit complete, 50 ml
- Basket for 20 receiver flasks (250 ml)
- Receiver flasks, 250 ml (set of 10)
- Kit for distillation by-pass
- Cable for connection of external titrator
- Kit for upgrade of Kjelttec 8200 Distillation Unit to Kjelttec 8400 Analyser Unit

DILACO[®]

Pérez Valenzuela 1138, Providencia
Tel.: (56) 2 2402 9700
www.dilaco.com

FOSS

Tel.: +45 7010 3370

info@foss.dk · www.fossanalytics.com

GB, June 2018